

in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: Mipa 2K-HS-Express-Klarlack CX 2

Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Clear coating material, Varnish

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Importer in New Zealand:

RJP Performance Coatings 33 Ha Crescent, Wiri Auckland 2104 Phone: 09 25000 91 Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand:

National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 1 H360 May damage fertility or the unborn child.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

n-Butyl acetate

5-methylhexan-2-one

2-Methoxy-1-methylethyl acetate

Reaction mass of pentamethyl-piperidylsebacate

· Hazard statements

H226 Flammable liquid and vapour.



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-Butyl acetate	25-50%
	🚸 Flam. Liq. 3, H226; 🕚 STOT SE 3, H336	
763-69-9	Ethyl 3-ethoxypropionate	2.5-<10%
	♦ Flam. Liq. 3, H226	
110-12-3	5-methylhexan-2-one	≥2.5-<3%
	♦ Flam. Liq. 3, H226; ♦ Repr. 2, H361; ♦ Acute Tox. 4, H332	
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
	🚸 Flam. Liq. 3, H226; 伙 STOT SE 3, H336	
1065336-91-5	Reaction mass of pentamethyl-piperidylsebacate	≥0.25-<1%
	Repr. 2, H361; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1A, H317	
77-99-6	1,1,1-Trimethylolpropane	<1%
	Repr. 2, H361	
7575-23-7	Pentaerythritol tetrakis(3-mercaptopropionate)	≥0.1-<0.25%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1A, H317	
3648-18-8	dioctyltin dilaurate	<0.3%
	♠ Repr. 1, H360; STOT RE 1, H372	

·SVHC

3648-18-8 dioctyltin dilaurate

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 2)

· After skin contact: Immediately rinse with water.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 4)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:		
123-86-4 n-Butyl acetate		
WES (New Zealand)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm	
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm	
110-12-3 5-methylhexan-2-one		
WES (New Zealand)	Long-term value: 234 mg/m³, 50 ppm	
IOELV (EU)	Long-term value: 95 mg/m³, 20 ppm	
108-65-6 2-Methoxy-1-methylethyl acetate		
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin	

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined. · Initial boiling point and boiling range: 124-128 °C

• Flash point: 27 °C (DIN EN ISO 1523:2002)

• Flammability (solid, gas): Flammable. • Auto-ignition temperature: 370 °C (DIN

• Auto-ignition temperature: 370 °C (DIN 51794) • Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
Upper: 7.5 Vol %
Vapour pressure at 20 °C: 10.7 hPa
Vapour pressure at 50 °C: 55 hPa

Density at 20 °C: 1.005 g/cm³ (DIN EN ISO 2811-1)

Relative density
Vapour density
Evaporation rate
Not determined.
Not determined.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic at 20 °C: 20-23 s (DIN 53211/4)

· Solvent content:

VOC (EC) 41.83 %
Solids content (weight-%): 58.2 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 5)

· Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity May damage fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · NZS, IMDG, IATA

UN1263

(Contd. on page 7)



in accordance with HSNO

Revision: 26.09.2023 Printing date 28.09.2023 Version number 19

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 6)

· UN proper shipping name

UN1263 PAINT

· IMDG, IATA **PAINT**

· Transport hazard class(es)

· NZS



· Class 3 (F1) Flammable liquids.

·Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· Packing group

· NZS, IMDG, IATA Ш

· Environmental hazards:

· Marine pollutant: Yes

Warning: Flammable liquids. · Special precautions for user

Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

· Stowage Category Α

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 5L · Transport category 3 Tunnel restriction code D/E

· Limited quantities (LQ) 5L

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· HSNO Approval numbers	
123-86-4 n-Butyl acetate	HSR001091
110-12-3 5-methylhexan-2-one	HSR001200

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 8)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 7)

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

n-Butyl acetate

5-methylhexan-2-one

2-Methoxy-1-methylethyl acetate

Reaction mass of pentamethyl-piperidylsebacate

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662. Refer also to the Site & Storage requirements document.

· Substances of very high concern (SVHC) according to REACH, Article 57

3648-18-8 dioctyltin dilaurate

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 9)



in accordance with HSNO

Printing date 28.09.2023 Version number 19 Revision: 26.09.2023

Trade name: Mipa 2K-HS-Express-Klarlack CX 2

(Contd. of page 8)

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Contact:

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1: Reproductive toxicity – Category 1 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3