PAINTRUTS BODYSHOP SUPPLIES



SAFETY DATA SHEET PRE-MIXED 1K CAR PAINT PRINTING DATE 06.08.2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

- · 1.1 Product identifier
- · Trade name: Mipa BC 2-Schicht-Basislack mixed with Mipa BC -Converter
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: HAZARDS IDENTIFICATION

[•] 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labelling:* n-Butyl acetate 2-Methoxy-1-methylethyl acetate Hydrocarbons, C9, aromatics Methyl ethyl ketone

(Contd. of page 1)

· Hazard statements					
H226 Flammable liquid and vapour.					
H336 May cause drowsiness or dizziness.					
H412 Harmful to aquatic life with long lasting effects.					
Precautionary statements					
P210 Keep away from heat, hot surfaces, sparks, o sources. No smoking.	open flames and other ignition				
P261 Avoid breathing dust/fume/gas/mist/vapours/spra	<i><i></i></i>				
P280 Wear protective gloves/protective clothing/eye pl protection.					
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all co with water [or shower].	ontaminated clothing. Rinse skin				
P304+P340 IF INHALED: Remove person to fresh air and kee P312 Call a POISON CENTER/doctor if you feel unwel	· •				
· Additional information:					
EUH066 Repeated exposure may cause skin dryness or cracking.					
EUH208 Contains Fatty acids, C14-18 and C16-18-unsatd., male reaction.	eated. May produce an allergic				
· 2.3 Other hazards					
Results of PBT and vPvB assessment					

• PBT: Not applicable.
 • vPvB: Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-Butyl acetate	25-50%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone Flam. Liq. 2, H225;	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene 🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1,	<2.5%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	<i>≥</i> 0.1-<1%

SECTION 4: FIRST AID MEASURES

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: FIREFIGHTING MEASURES

- · 5.1 Extinguishing media
- [.] Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: HANDLING AND STORAGE

• **7.1 Precautions for safe handling** Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

(Contd. of page 3)

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs. Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

	8.1 Control parameters				
-	Ingredients with limit values that require monitoring at the workplace:				
	6-4 n-Butyl acetate				
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm				
1330-	20-7 Xylene				
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV				
108-6	5-6 2-Methoxy-1-methylethyl acetate				
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk				
78-93	-3 Methyl ethyl ketone				
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV				
100-4	1-4 Ethylbenzene				
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk				
· Ingre	dients with biological limit values:				
1330-	20-7 Xylene				
BMG	/ 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid				
78-93	-3 Methyl ethyl ketone				
BMG	/ 70 µmol/L Medium: urine Sampling time: post shift Parameter: butan ?-on				
· Addit	ional information: The lists valid during the making were used as basis.				
· 8.2 E · Appro · Indivi · Gene Imme	xposure controls opriate engineering controls No further data; see section 7. idual protection measures, such as personal protective equipment ral protective and hygienic measures: diately remove all soiled and contaminated clothing hands before breaks and at the end of work.				

(Contd. of page 4)

• **Respiratory protection:** Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: \geq 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material Value for the permeation: Level ≤ 1

Eye/face protection



Tightly sealed goggles

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- [•] 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- Colour:
- · Odour:
- Odour threshold:
- · Melting point/freezing point:
- Boiling point or initial boiling point and boiling range
- · Flammability
- · Lower and upper explosion limit
- · Lower:
- · Upper:
- · Flash point:
- · Auto-ignition temperat. . e
- · Decomposition temper_...rc:
- · pH
- · Viscosity:
- · Kinematic viscosity at 20 °C
- · Dynamic:

Fluid According to product specification Characteristic Not determined. Undetermined.

124-128 °C (123-86-4 n-Butyl acetate) Flammable.

1.2 Vol % (123-86-4 n-Butyl acetate) 7.5 Vol % (123-86-4 n-Butyl acetate) ここ °つ (つい こここう) ここ (つい ここうこう) こここうこ た.i..c.i. Not determined.

130-140 s (DIN 53211/4) Not determined.

 Solubility water: Partition coefficient n-octanol/water (log value) Vapour pressure at 20 °C: Vapour pressure at 50 °C: Density and/or relative density Density at 20 °C: 	Not miscible or difficult to mix. Not determined. 10.7 hPa (123-86-4 n-Butyl acetate) 55 hPa 1.012 g/cm³ (DIN 53217)
 Partition coefficient n-octanol/water (log value) Vapour pressure at 20 °C: Vapour pressure at 50 °C: Density and/or relative density 	Not determined. 10.7 hPa (123-86-4 n-Butyl acetate) 55 hPa
value) · Vapour pressure at 20 °C: · Vapour pressure at 50 °C: · Density and/or relative density	10.7 hPa (123-86-4 n-Butyl acetate) 55 hPa
 Vapour pressure at 20 °C: Vapour pressure at 50 °C: Density and/or relative density 	10.7 hPa (123-86-4 n-Butyl acetate) 55 hPa
 Vapour pressure at 20 °C: Vapour pressure at 50 °C: Density and/or relative density 	55 hPa
· Vapour pressure at 50 °C: · Density and/or relative density	55 hPa
Density and/or relative density	1.012 g/cm³ (DIN 53217)
	1.012 g/cm³ (DIN 53217)
Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
Form:	Fluid
Important information on protection of heal	lth
and environment, and on safety.	
 Ignition temperature: 	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	54.04 %
Solids content (weight-%):	46.0 %
Change in condition	
Evaporation rate	Not determined.
•	
Information with regard to physical haza classes	10
	Void
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
[.] Flammable liquids	Flammable liquid and vapour.
[.] Flammable solids	Void
• Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
• Oxidising solids	Void
^o Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. of page 6)

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA
- 14.2 UN proper shipping name
- · ADR · IMDG, IATA

UN1263 PAINT PAINT

UN1263

 14.3 Transport hazard class(es) 	
ADR	
3	
Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
3	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards:	
· Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
 Transport/Additional information: 	
· ADR	
· Limited quantities (LQ)	5L
 Transport category Tunnel restriction code 	3 D/E
· Remarks:	≤ 450 l: 2.2.3.1.5 ADR
·IMDG	
Limited quantities (LQ)	5L
· Remarks:	≤ 30 l: 2.2.3.5 IMDG-Code
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[.] Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2 Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 * Data compared to the province version altered

END OF DOCUMENT