

# Technical Data Sheet



## ULTRABLEND

UltraBlend is a technically advanced blending clear, that dissolves the edges of clear coats and solid colours. Can be used with HS and MS coatings. Ideal for smart repairs. 100% U.V. stable. Drying time of 15-30 minutes.

Code - ULTRABLEND



**proxl.com**

Visit our website  
for more products



## Technical Data

### Technical Information

Size	500ml
Basis of binder	Special Resin blend
VOC Directive	2004/42/II B(e),(840)
VOC content	751g/l
Storage stability	Store in a cool dry place in original container between -10°C & +25°C
Shelf Life	10 years if appropriate storage provided (=10°- 25°C, relative air humidity of max. 60%)

## Substrates





- Solvent based clear lacquers and top coats

## Surface Preparation

- Surface in transition zone should be sanded until matt with P 2000 - P 4000
- For professional use only
- Wear an appropriate respirator (recommended type A2/P3)

## Application Guide

Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %

1 	Shake aerosol for at least two mins, after agitator ball is free
2 	Apply in cross coats from distance of 150 - 250mm from object
3 	Apply several 1 - 2 light spray passes to the edge of the blending area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.
4 	After use, turn aerosol upside down and empty valve

## **DISPOSAL**

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed of as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

## **ENVIRONMENTAL**

ProXL is committed to use formulations without restricted or critical ingredients and to achieve the best possible performance. The caps and packagings are made of recyclable material.

### **DISCLAIMER OF LIABILITY**

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.