

Page 1/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol 1K Unifill S1 weiss
- · (Article number) product ID.: REZ1309
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 1)

#### · Hazard pictograms





GHS02 GH

#### · Signal word Danger

#### · Hazard-determining components of labelling:

acetone

maleic anhydride methyl acetate

butanone

Fatty acids, C14-18 and C16-18-unsatd., maleated

#### · Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

*P103 Read carefully and follow all instructions.* 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

*P251* Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

 $Without\ adequate\ ventilation,\ explosive\ atmosphere/gas\ mix\ may\ be\ created.$ 

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

		(Contd. of page
Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⑤ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; ( Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-xxxx	methyl acetate  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone <b>♦</b> Flam. Liq. 2, H225; <b>♦</b> Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<5%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane ♠ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♠ Skin Irrit. 2, H315; STOT SE 3, H336	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226;  STOT SE 3, H336	1-<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers  Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19-xxxx	Fatty acids, C14-18 and C16-18-unsatd., maleated  Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene	<1%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	propylene glycol monomethyl ether acetate  Flam. Liq. 3, H226;  STOT SE 3, H336	<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride ♠ Resp. Sens. 1, H334; STOT RE 1, H372; ♠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.19

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 3)

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- $\cdot \textbf{7.3 Specific end use}(s) \ \textit{No further relevant information available}.$

GB

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 4)

	ontrol parameters
_	dients with limit values that require monitoring at the workplace:
	0-6 dimethyl ether
WEL	Short-term value: 958 mg/m³, 500 ppm
<b>(5.</b> (.)	Long-term value: 766 mg/m³, 400 ppm
	f-1 acetone
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
70-20	2-9 methyl acetate
	Short-term value: 770 mg/m³, 250 ppm
WLL	Long-term value: 616 mg/m³, 200 ppm
<b>78-9</b> 3	B-3 butanone
WEL	Short-term value: 899 mg/m³, 300 ppm
_	Long-term value: 600 mg/m³, 200 ppm
	Sk, BMGV
110-8	32-7 cyclohexane
WEL	Short-term value: 1050 mg/m³, 300 ppm
	Long-term value: 350 mg/m³, 100 ppm
	65-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm
	Long-term value: 274 mg/m³, 50 ppm Sk
1330.	-20-7 xylene, mixture of isomers
	Short-term value: 441 mg/m³, 100 ppm
	Long-term value: 220 mg/m³, 50 ppm
	Sk; BMGV
100-4	11-4 ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm
	Long-term value: 441 mg/m³, 100 ppm
100	Sk
	65-6 propylene glycol monomethyl ether acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm
	Sk
108-3	B1-6 maleic anhydride
	Short-term value: 3 mg/m³
	Long-term value: 1 mg/m³
	Sen
Ingre	dients with biological limit values:
<b>78-9</b> 3	3-3 butanone
BMG	V   70 μmol/L
	Medium: urine
	Sampling time: post shift Parameter: butan-2-one

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 5)

### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

#### · Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state

Aerosol

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

(Contd. on page 7)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

	(Contd. of page 0
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	-24.9 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	2.6 Vol % (67-64-1 acetone)
· Upper:	18.6 Vol % (115-10-6 dimethyl ether)
· Flash point:	<0 °C
· Auto-ignition temperature:	235 °C (115-10-6 dimethyl ether)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
Solubility	N
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
Density and/or relative density	0.949 ~/1
Relative density	0.848 g/ml Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health an	d
environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	<b>5</b> 0.0 %
· Organic solvents:	79.9 %
YOR (BY)	With propellant gas. Content given by weight.
$\cdot VOC(EU)$	(<840g/l)
~ ***	79.91 %
Solids content:	18.2 %
Change in condition	M . P 11
· Evaporation rate	Not applicable.
Information with regard to physical hazard classe	es
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	
gases in contact with water	Void
· Oxidising liquids	Void

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 7)

· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 8)

- Uncleaned packaging:
   Recommendation: Disposal must be made according to official regulations.

UN1950
0111730
1050 AEROGOLG
1950 AEROSOLS
AEROSOLS AEROSOLS, flammable
AEKOSOLS, jiamimabie
2 5F Gases.
2.1
2.1 Gases.
2.1 2.1
Void
not classified
No
Warning: Gases.
not classified
F-D,S-U
SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of
litre: Category A. For AEROSOLS with a capacity above
1 litre: Category B. For WASTE AEROSOLS: Category
C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of
litre:
Segregation as for class 9. Stow "separated from" class
except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2
For WASTE AEROSOLS:

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

	(Contd. of page
· 14.7 Maritime transport in bulk according transfer in bulk according to the second contract of the second contra	ling to IMO Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet may only be passed on to third parties for the manufacturer's brands.

(Contd. on page 11)

Version number 1 Revision: 08.12.2023 Printing date 08.12.2023

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 10) · Relevant phrases Extremely flammable gas. H220 H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH018 In use may form flammable/explosive vapour-air mixture. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract. · Department issuing SDS: Product safety department · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative ATE: Acute toxicity estimate values Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 : Aerosols – Category 3 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2