Printing date 29.03.2015 Revision: 29.03.2015

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci 1K Filler
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture 1263
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings

Industrial Zone El - Raswa

Port Said

EGYPT

mohamed.rashad@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R48/20-63-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Xi; Irritant

R36/38: Irritating to eyes and skin.



F; Highly flammable

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS05

GHS07

S07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

butanol

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.
IF IN EYES: Rinse cautiously with

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

CAS: 108-88-3	toluene	1td. of page 2
	Xn R48/20-63-65; Xi R38; → F R11 R67	23 3076
	Repr. Cat. 3	
	🏇 Flam. Liq. 2, H225; 🗞 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; 🕎 Skin Irrit. 2, H315; STOT SE 3, H336	-
CAS: 123-86-4	n-butyl acetate	2-12%
EINECS: 204-658-1	R10-66-67	
	🊸 Flam. Liq. 3, H226; 伙 STOT SE 3, H336	
CAS: 78-83-1	butanol	2-12%
EINECS: 201-148-0	Xi R37/38-41 R10-67	
	🏇 Flam. Liq. 3, H226; 💠 Eye Dam. 1, H318; 🕠 Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 111-76-2	2-butoxyethanol	2-12%
EINECS: 203-905-0	X n R20/21/22; X Xi R36/38	
	(1) Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 78-93-3	butanone	≤ 2.5%
EINECS: 201-159-0	X i R36; № F R11 R66-67	
	🏇 Flam. Liq. 2, H225; か Eye Irrit. 2, H319; STOT SE 3, H336	1

4 First aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- $\cdot \textit{After skin contact:} \ Immediately \ wash \ with \ water \ and \ soap \ and \ rinse \ thoroughly.$
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace
--

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

(Contd. on page 5)

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 4)

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk. BMGV

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

· Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

GB

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 5)

	rties
Information on basic physical and General Information Appearance:	chemical properties
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	108 °C
Flash point:	4 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	29 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	73.5 %
VOC (EC)	73.50 %
Solids content:	26.5 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

.]	LD/LC50	values	relevant	for	classi	fication:
-----	---------	--------	----------	-----	--------	-----------

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal		12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitisation: No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GE

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 7)

Transport information	
UN-Number	11311.372
ADR, IMDG, IATA	UN1263
UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
Transport hazard class(es)	
· ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
· ADR, IMDG, IATA	II
Environmental hazards:	
· Marine pollutant:	No
-	
Special precautions for user	Warning: Flammable liquids. 33
Danger code (Kemler): EMS Number:	55 F-E,S-E
	1
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	пот аррисаотс.
· ADR · Limited quantities (LQ)	5L
Excepted quantities (EQ)	SL Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 50 ml
Transport category	2
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
- · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UNI 263, PAINT, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Printing date 29.03.2015 Revision: 29.03.2015

Trade name: Kapci 1K Filler

(Contd. of page 8) · Relevant phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. R10 Flammable. *R11* Highly flammable. R20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R37/38 Irritating to respiratory system and skin. R38 Irritating to skin. R41 Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation. R48/20 R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. · Department issuing MSDS: Product safety department · Contact: Mr. Rashad · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

GB