








### Intended use

PUR Plus-Härter A 60 is a special 2K hardener for use with Mipa 2K industrial coatings and Mipa 2K paints that are applied by brush.

### Processing instructions

	<b>Mixing ratio</b> <b>hardener</b> see basic product					
			<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>		
			—	—		
	<b>Hardener</b> —					
	<b>Pot life</b> see basic product					
	<b>Thinner</b> see basic product					
	<b>Spray viscosity</b> see basic product <b>gravity spray gun</b> —					
				<b>Airmix/Airless</b>		
				—		
	<b>Application mode</b> <b>application mode</b> see basic product					
	<b>hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>dilution</b>	
	—	—	—	—	—	
	<b>Drying time</b> <b>hardener</b> see basic product					
	<b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	—	—	—	—	—	—

### Note

**Characteristics:**

binder base:	polyisocyanate
solids content (% by weight):	76 - 77
solids content (% by volume):	—
delivery viscosity DIN 53211 4 mm (in s):	33 - 34 s
density DIN EN ISO 2811 (kg/l):	1,0 - 1,1
gloss level ISO 2813 at 60° (GU):	see basic product

**Properties:** see basic product

**Theoretical spreading rate :** see basic product

<b>Storage:</b>	for approx. 2 years in unopened original container.
<b>VOC Regulation :</b>	see basic product
<b>Processing conditions:</b>	see basic product
<b>Substrate preparation:</b>	see basic product
<b>Proposed coating structure:</b>	see basic product
<b>Special notes:</b>	For professional use only.
<b>Cleaning of tools:</b>	Clean tools immediately after use with Mipa Nitroverdünnung .