

## TECHNICAL DATA SHEET



### ULTIMATE UV Primer - Aerosol

Date: 15-Nov-2023

**DESCRIPTION**

**ULTIMATE UV Primer Aerosol** is a ready to use semi matt grey 1K UV Acrylic Filler Primer. It has excellent adhesion on metals with excellent UV curing speed even with UV-A (LED) lamps. The UV Primer aerosol has excellent sandability and corrosion resistance. It is suitable for application on steel, aluminium and galvanised metals. For plastics a plastic primer is needed prior to application of UV.

**Composition:** Acrylic Resins  
**Colour:** Grey  
**Shelf life:** Correctly stored material, in a cool dry place will have a shelf life of 12 months  
**Pack size:** 400ml Aerosol

	Health and safety “For professional use only” Important: When using any new product, consult the “Health and Safety” data sheet. Always read the risks and precautions stated on the product label.
	Clean surface thoroughly using slow or fast degreaser.
	Shake can well before use 2-3 minutes.
	Apply product spraying 15-20cm away from the panel being sprayed. DO NOT overload product onto the panel.
	Apply 1 light coat followed by a 30 second flash off. Apply a full coat followed by 1 minute flash off. Apply a full coat followed by 2 minutes flash off.
	UV A (LED) – lamp time for 2 ½ minutes. If the product is tacky you can wipe with thinners, this is not a requirement. Dry film thickness up to 120 microns. Always wear UV glasses. These times may vary dependent on the size of the repair and UV lamp being used.

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.