according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: P 99 Multi Star
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: +49(0)700 24112112 (MIP)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: styrene
- · Hazard statements

H226 Flammable liquid and vapour.

(Contd. on page 2)

according to 1907/2006/EC, Article 31



Version number 175 Printing date 25.05.2020 Revision: 25.05.2020

Trade name: P 99 Multi Star

(Contd. of page 1)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

· Additional information:

EUH208 Contains 2,2'-[(4-methylphenyl)imino]bisethanol, 2,2'-(m-tolylimino)diethanol. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:                        |  |              |
|--|--|--------------|
| EINECS: 202-851-5<br>Reg.nr.: 01-2119457861-32 | styrene  Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 | ≥10-≤20%     |
| CAS: 38668-48-3<br>EINECS: 254-075-1           | 1,1'-(p-tolylimino)dipropan-2-ol Acute Tox. 2, H300; Dege Irrit. 2, H319; Aquatic Chronic 3, H412  | <1%          |
| EINECS: 221-359-1                              | 2,2'-[(4-methylphenyl)imino]bisethanol  Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412  | ≥0.1-<1%     |
| EINECS: 202-114-8                              | 2,2'-(m-tolylimino)diethanol<br>STOT RE 2, H373; Eye Dam. 1, H318; Nacute Tox. 4,<br>H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317  | ≥0.1-<1%     |
| CAS: 117-80-6<br>EINECS: 204-210-5             | dichlone (ISO)  Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317  | ≥0.025-<0.1% |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

Trade name: P 99 Multi Star

(Contd. of page 2)

## SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Information for doctor:

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- **Protective equipment:** Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



*Printing date 25.05.2020 Version number 175 Revision: 25.05.2020* 

Trade name: P 99 Multi Star

(Contd. of page 3)

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves (EN 374)

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7$  mm

- Breakthrough time of glove material Value for the permeation: Level  $\leq 6$
- · Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Viscous Colour: Beige

(Contd. on page 5)

# **Safety data sheet** according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

Trade name: P 99 Multi Star

|   | (Contd. of page  |
|---|--|
| Odour:                                  | Characteristic   |
| Odour threshold:                        | Not determined.  |
| · pH-value:                             | Not determined.  |
| Change in condition                     |  |
| Melting point/freezing point:           | Undetermined.  |
| Initial boiling point and boiling range |  |
| Flash point:                            | 34 °C (DIN 53213)  |
| · Flammability (solid, gas):            | Not applicable.  |
| Ignition temperature:                   | 480 °C (DIN 51794)   |
| Decomposition temperature:              | Not determined.  |
| · Auto-ignition temperature:            | Product is not selfigniting.                                 |
| Explosive properties:                   | Product is not explosive. However, formation of explosive at |
|   | vapour mixtures are possible.                                |
| Explosion limits:                       |  |
| Lower:                                  | 1.2 Vol %  |
| Upper:                                  | 8.9 Vol %  |
| · Vapour pressure at 20 °C:             | 6 hPa  |
| Density at 20 °C:                       | 1.801 g/cm³ (DIN 53217)                                      |
| · Relative density                      | Not determined.  |
| · Vapour density                        | Not determined.  |
| Evaporation rate                        | Not determined.  |
| · Solubility in / Miscibility with      |  |
| water:                                  | Not miscible or difficult to mix.                            |
| Partition coefficient: n-octanol/water: | Not determined.  |
| · Viscosity:                            |  |
| Dynamic at 20 °C:                       | 70,000-80,000 mPas   |
| Kinematic:                              | Not determined.  |
| Solvent content:                        |  |
| VOC (EC)                                | 0.49 %   |
| Solids content (weight-%):              | 84.4 %   |
| 9.2 Other information                   | No further relevant information available.                   |

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

Trade name: P 99 Multi Star

(Contd. of page 5)

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 100-42-5 styrene

| Oral       | LD50     | 5,000 mg/kg (rat)  |
|------------|----------|--------------------|
|            | LD50     | >2,000 mg/kg (rat) |
| Inhalative | LC50/4 h | 11.8 mg/l (rat)    |

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eve irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 7)

# **Safety data sheet** according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

Trade name: P 99 Multi Star

(Contd. of page 6)

- Uncleaned packaging:
   Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport informat                                      |   |
|---|---|
| 14.1 UN-Number<br>ADR, IMDG, IATA                                   | UN3269  |
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA                   | UN3269 POLYESTER RESIN KIT<br>POLYESTER RESIN KIT |
| 14.3 Transport hazard class(es)                                     |   |
| ADR   |   |
| Class<br>Label  | 3 (F3) Flammable liquids.                         |
| IMDG, IATA  Class   | 3 Flammable liquids.                              |
| Label 14.4 Packing group ADR, IMDG, IATA                            | III   |
| 14.5 Environmental hazards:<br>Marine pollutant:                    | No  |
| 14.6 Special precautions for user                                   | Warning: Flammable liquids.                       |
| Danger code (Kemler): EMS Number: Stowage Category                  | -<br>F-E,S-D<br>A                                 |
| 14.7 Transport in bulk according to Anno<br>Marpol and the IBC Code | ex II of<br>Not applicable.                       |
| Transport/Additional information:                                   |   |
| ADR<br>Transport category<br>Tunnel restriction code                | 3<br>E  |
| IMDG<br>Limited quantities (LQ)                                     | <i>5L</i>   |
| UN "Model Regulation":  | UN 3269 POLYESTER RESIN KIT, 3, III               |

according to 1907/2006/EC, Article 31



Printing date 25.05.2020 Version number 175 Revision: 25.05.2020

Trade name: P 99 Multi Star

(Contd. of page 7)

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

| Class | Share in % |
|-------|------------|
| I     | <1         |
| NK    | 10-25      |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H300 Fatal if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 9)

# **Safety data sheet** according to 1907/2006/EC, Article 31



Printing date 25.05.2020

Trade name: P 99 Multi Star

Version number 175

Revision: 25.05.2020

(Contd. of page 8)

Acute Tox. 2: Acute toxicity - Category 2

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
\*\* Data compared to the previous version altered.