



SPRAY MASK A1P2

GENERAL

CODE	DESCRIPTION
SMA1P2	Spray mask A1P2



DESCRIPTION

Spray mask that protects against inhalation of isocyanates, from paint or solvents. The mask fits snugly around nose and mouth. This PPE is designed to protect against hazards that can cause irreparable damage to health. Each mask comes in an airtight storage box with two A1 carbon filters and two P2 pre-filters. Replacement is necessary after a period of use of up to 40 hours. Complies with the UNE-EN 140 standard and is CE-certified under number 0159.

FEATURES

- High-grade silicon material improves comfort and durability
- Dual-mode headband for easy adjustment, divided into standard mode and pull-down mode
- The exhalation valve valve sleeve guides the exhaled air and water vapor down, thereby reducing the generation of fog
- resistant against formaldehyde and isocyanates

ADVANTAGES

- Specially designed for car painters.
- Carbon filters protect against spray mist and possible isocyanates (if used according to regulations).
- Made of flexible plastic that moulds well to the face, preventing leaks and ensuring high wearing comfort.
- The fit can be adjusted with the adjustable headband and neck clip.
- Large filter area with two carbon filters for optimal protection and easy breathing.
- Large exhalation valve for optimal breathing.
- Transparent, airtight storage box extends the life of the carbon filters.

TECHNICAL INFORMATION

Type	Half-mask spray mask
Valves	Two carbon filters one exhalation valve
Strap material	Polyester/latex elastic
Material headband	Adjustable headband with neck clip
Material inhalation valve	Silicone, colour blue
Material exhalation valve	Natural rubber
Material rest of mask	Flexible plastic; colour blue