

in accordance with HSNO

Revision: 25.09.2023 Printing date 28.09.2023 Version number 25

## 1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: Mipa Multi-Mat
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint additive
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Importer in New Zealand:

**RJP Performance Coatings** 33 Ha Crescent, Wiri Auckland 2104 Phone: 09 25000 91 Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand:

National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

## 2 Hazards identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07

- Signal word Warning
- · Hazard-determining components of labelling:

2-Methoxy-1-methylethyl acetate

**Xylene** 

Ethylbenzene

Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3propanediamine

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

| · Dangerous o | Dangerous components:  |          |  |
|---------------|--|----------|--|
| 112-07-2      | 2-Butoxyethyl acetate  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Flam.  Liq. 4, H227   | 25-50%   |  |
| 108-65-6      | 2-Methoxy-1-methylethyl acetate  Tlam. Liq. 3, H226;  STOT SE 3, H336  | 10-25%   |  |
| 1330-20-7     | Xylene  ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319      | 5-<10%   |  |
| 100-41-4      | Ethylbenzene  Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | <2.5%    |  |
| 8002-74-2     | Paraffin waxes and Hydrocarbon waxes   | <2.5%    |  |
| 162627-17-0   | Fatty acids,C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and1,3-propanediamine  Skin Sens. 1A, H317                         | ≥0.1-<1% |  |

Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

### 112-07-2 2-Butoxyethyl acetate

IOELV (EU) Short-term value: 333 mg/m³, 50 ppm

Long-term value: 133 mg/m³, 20 ppm

Skin

(Contd. on page 4)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

|                      |   | (Contd. of page 3 |
|----------------------|---|-------------------|
| 108-65-6 2-Methoxy-  | 1-methylethyl acetate   |                   |
| IOELV (EU)           | Short-term value: 550 mg/m³, 100 ppm<br>Long-term value: 275 mg/m³, 50 ppm<br>Skin    |                   |
| 1330-20-7 Xylene     |   |                   |
| WES (New Zealand)    | Long-term value: 217 mg/m³, 50 ppm<br>oto   |                   |
| IOELV (EU)           | Short-term value: 442 mg/m³, 100 ppm<br>Long-term value: 221 mg/m³, 50 ppm<br>Skin    |                   |
| 100-41-4 Ethylbenze  | ne  |                   |
| WES (New Zealand)    | Short-term value: 176 mg/m³, 40 ppm<br>Long-term value: 88 mg/m³, 20 ppm<br>skin, oto |                   |
| IOELV (EU)           | Short-term value: 884 mg/m³, 200 ppm<br>Long-term value: 442 mg/m³, 100 ppm<br>Skin   |                   |
| 8002-74-2 Paraffin w | axes and Hydrocarbon waxes  |                   |
| WES (New Zealand)    | Long-term value: 2 mg/m³  |                   |

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: 137-143 °C
 Flash point: 30 °C (DIN 53213)
 Flammability (solid, gas): Flammable.

• Auto-ignition temperature: 280 °C (DIN 51794)
• Decomposition temperature: Not determined.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol %
 Upper: 10.8 Vol %
 Vapour pressure at 20 °C: 6.7-8.2 hPa

Density at 20 °C: 1.074 g/cm³ (DIN 53217)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic at 20 °C: 10,000 mPas • Kinematic: Not determined.

· Solvent content:

· VOC (EC) 60.20 % Solids content (weight-%): 39.8 %

· Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:
   No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



in accordance with HSNO

Revision: 25.09.2023 Printing date 28.09.2023 Version number 25

Trade name: Mipa Multi-Mat

· Hazardous decomposition products: Carbon monoxide

(Contd. of page 5)

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

· UN-Number

· NZS, IMDG, IATA UN1263

· UN proper shipping name

· NZS

UN1263 PAINT RELATED MATERIAL · IMDG, IATA PAINT RELATED MATERIAL

(Contd. on page 7)



in accordance with HSNO

Revision: 25.09.2023 Printing date 28.09.2023 Version number 25

Trade name: Mipa Multi-Mat

(Contd. of page 6)

· Transport hazard class(es)

· NZS



3 (F1) Flammable liquids. · Class

· Label

· IMDG, IATA



3 Flammable liquids. · Class

· Label 3

· Packing group

· NZS, IMDG, IATA Ш

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E Α

· Stowage Category

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· NZS

· Limited quantities (LQ) 5L · Transport category 3 Tunnel restriction code D/E ≤450 l: -· Remarks:

· IMDG

· Limited quantities (LQ) 5L · Remarks: ≤30 l: -

· UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

|   | · HSNO Approval numbers |                       |           |  |
|---|-------------------------|-----------------------|-----------|--|
| ſ | 112-07-2                | 2-Butoxyethyl acetate | HSR001155 |  |
| Ī | 1330-20-7               | Xylene                | HSR000983 |  |
| Ī | 100-41-4                | Ethylbenzene          | HSR001151 |  |

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 8)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

(Contd. of page 7)

#### · Hazard pictograms







GHS02 GHS07 GH

#### · Signal word Warning

#### · Hazard-determining components of labelling:

2-Methoxy-1-methylethyl acetate

**Xylene** 

Ethylbenzene

Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and1,3-propanediamine

#### · Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

#### · Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

#### · National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

### · Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662. Refer also to the Site & Storage requirements document.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H302 Harmful if swallowed.

(Contd. on page 9)



in accordance with HSNO

Printing date 28.09.2023 Version number 25 Revision: 25.09.2023

Trade name: Mipa Multi-Mat

(Contd. of page 8)

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### · Contact:

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.