

PURPLE TRANSLUCENT FINE LINE TAPE

TECHNICAL DATA SHEET 1113

V2.1 (01/25)

PRODUCT DESCRIPTION


JTAPE Purple Translucent Fine Line Tape uses a thermally stabilised, PVC backing with a rubber-based pressure sensitive adhesive, offering a higher grab than other fine line masking tapes.

It is highly flexible, translucent and easy to curve offering short-term UV resistance. After demasking, it will leave no residue and a sharp, clean separation line from surfaces in temperatures up to 150°C/302°F for up to 1 hour. Suitable for use with waterborne or solvent based paints.

PRODUCT CONSTRUCTION

Carrier

Adhesive



SHELF LIFE

12 months from date of receipt by customer when stored at 20°C ±5°C (68°F ±7°F) and 65% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	PVC
Adhesive	Rubber-based
Colour	Translucent Purple
Thickness	130µm / 0.130mm (±10%)
Width	1mm, 1.5mm, 2mm, 3mm, 6mm, 9mm, 12mm, 19mm, 25mm (±5%) etc. Other widths available on request.
Length	55m (2%).

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	8N/25mm	[ASTM D-1000]
Elongation at Break	230%	
Tensile Strength	37N/cm	[ASTM D-1000]
Temperature Resistance	150°C (302°F) for 1 hour	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.