according to 1907/2006/EC, Article 31

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Monofil Vario+ High Gloss Clearcoat
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Monofil Ltd. Aerosol System

Applied House, Fulflood Road

Leigh Park / Havant

Hampshire P09 5AX

GB-England

Tel.: 0044 2392 470909 Fax.: 0044 2392 470467

• 1.4 Emergency telephone number: Tel: 0044 2392 470909

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

butyl acetate

butan-1-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	butane Flam. Gas 1, H220; Press. Gas C, H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	propane Flam. Gas 1, H220; Press. Gas C, H280	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥10-≤20%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Nacute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥2.5-≤3%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

· Information for doctor:

(Contd. of page 2)

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 2 B

(Contd. on page 4)

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

. 0.1	control parameters
· Ingr	edients with limit values that require monitoring at the workplace:
106-	97-8 butane
WEL	Short-term value: 1810 mg/m³, 750 ppm
	Long-term value: 1450 mg/m³, 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
67-6	4-1 acetone
WEL	Short-term value: 3620 mg/m³, 1500 ppm
	Long-term value: 1210 mg/m³, 500 ppm
123-	86-4 butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm
	Long-term value: 724 mg/m³, 150 ppm
71-3	6-3 butan-1-ol
WEL	Short-term value: 154 mg/m³, 50 ppm
	Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 4)

 \cdot Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and c	chemical properties
General Information	
Appearance:	
Form: Colour:	Aerosol
Colour: Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: -44.5°C
Flash point:	-97°C (DIN EN ISO 1523:2002)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	365°C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
Vapour pressure at 20°C:	8,300 hPa
Density at 20°C:	0.723 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	07.60.0
VOC (EC)	87.60 %
Solids content (weight-%):	12.4 %
9.2 Other information	No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 5)

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

(Contd. on page 7)

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
$\cdot ADR$	UN1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1 2.1
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Danger code (Kemler):	Warning: Gases.
· EMS Number:	F- D , S - U
· Stowage Code	SWI Protected from sources of heat.
Ü	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS: Category C, Cle
	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr
	Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity
	above I litre: Segregation as for the appropria
	subdivision of class 2. For WASTE AEROSOL
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

· Transport/Additional information:		
· ADR		
· Transport category	2	
· Tunnel restriction code	D	
· <i>IMDG</i>		
· Limited quantities (LQ)	IL	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 9)

Printing date 08.11.2017 Version number 1 Revision: 08.11.2017

Trade name: Monofil Vario+ High Gloss Clearcoat

(Contd. of page 8)

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.