

GENERAL INFORMATION

TD80 Octobase Eco Degreaser is a specially developed degreaser for substrates to be coated with W00 - W999 Octobase Eco Plus System. Use wipe on/wipe off method, avoid evaporation of the TD80 Octobase Eco Degreaser to insure all the dirt is removed.

MIXING RATIO



GUN SET UP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

APPLICATION



FLASH OFF AND DRY TIMES



AIR DRY 20°C / 68°F		FORCED DRY 60°C / 140°F	
Flash off	-	Flash off	-
Dust free	-	Dust free	-
Dry to handle	-	Dry to handle	-
Dry to tape	-	Dry to tape	-
Dry to sand	-	Dry to sand	-
Dry to polish	-	Dry to polish	-

SUBSTRATES



POT LIFE AT 20°C / 68°F



COMPONENTS



ADDITIVES



SURFACE PREPARATION



NEXT LAYER



PHYSICAL DATA

EU REGULATIONS		
VOC Code	2004/42/IB(a)(200)199	
Product sub category (according directive 2004/42/EC) and max VOC content (ISO 11890-1/2) of the ready to use product.	IIB/a. Preparatory and cleaning - Pre-cleaner. EU limit values: 200 g/l. (2007) This product contains a maximum of 199 g/l VOC.	
Chemical Base	Mix of water and organic solvents	
Physical Properties	Viscosity (RTS)	-
	Specific Gravity (kg/l)	0,973
	Flash Point Closed Cup	41°C / 105,8°F
	Volume % Solids	-
	Economy	-
	Gloss	-
	Colour	-

PROTECTION

Use suitable respiratory protection (*fresh air supply respirator is strongly recommended*).



For more detailed information please visit the following link for the Safety Data Sheet:

https://sds.octoral.com/en/octoral/choose_localization

CLEAN UP



STORAGE/SHELF LIFE

Minimum 5 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).



NOTES

Do not use as Gun Cleaner.