

PRODUCT: AWESOME Body Filler

PN: 104293 3L

DESCRIPTION: Engineered for effortless mixing and a smooth, creamy application. Superior vertical hold allows for application in heavier layers. Spreads easily and sands quickly to a pinhole-free finish

APPROVED

SUBSTRATES: Steel, Galvanized Steel, Aluminum, Fibreglass, Zinc Coated Steel, Hard Plastics & Polyester Fillers




For structural repairs prone to high degrees of stress and flexibility, use a fibre reinforced filler such as Everglass® or Fiber Tech®.

PREPARATION:



- Clean and degrease the entire panel to be repaired, followed by a mild cleaning solvent. Surface must be thoroughly dry before repairing or applying material.
- Keep the repair area small. Use 80-180 grit to remove the paint and featheredge.

MIXING:



- Stir the filler before using. Knead the cream hardener.
- Measure hardener 2% by weight, add a ribbon of cream hardener from edge to edge across the center of a 10 cm diameter puddle (refer to tin lid).
- Puddles larger than 10 cm in diameter will require additional hardener.
- Mix thoroughly until uniform color is achieved.

APPLICATION:



- Apply in layers with even firm pressure.
- Do not apply all at once.

FINISH:



- Rough shape with 80 grit (as needed)
- Sand filler with 80-180 grit or finer
- Final sand repair and paint edge 180 grit.

For best results, apply a premium Evercoat polyester putty to provide a smoother finish and reduce the amount of primer surfacer needed for a quality finish.

TECHNICAL SPECIFICATION:

Appearance	Smooth Gold Colored Paste
VOC	Refer to Section 9 of the Safety Data Sheet
Relative Density	Refer to Section 9 of the Safety Data Sheet
Work Time	3-5 minutes @ 22° C
Sand Time	15-20 minutes @ 22°C
Max Recommended Thickness (sanded)	6mm

Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat® products. Safety Data Sheets can be found online at evercoat.com.

NOTES:

Never return mixed filler to can

Keep can closed and store in a cool dry place

USE WITH EVERCOAT CREAM HARDENER ONLY!